

Mini Skid



Model	Gallons per day	Liters per day
MS-1	1,500	5,625
MS-2	3,000	11,250

The Mini Skid is a smaller version of our Diamond Skid. This economical purification system has everything needed to produce and deliver pure drinking water. The system will work well for a mini water store, bottling plant or as an add-on to an existing business. Due to the Mini Skid compact size, it takes up less floor space and will interface with additional compatible units to accommodate your everyday business need.

Purification Process:

STEP 1: Carbon - an activated carbon cartridge filter that removes chlorine, chloramine, solvents, lead, insecticides, gases, and other harmful contaminants. Works as a water softener, without the use of salt and drawing hardness particles together and crystallizing them. Includes an automatic backwashing system.

STEP 2: 5 Micron Pre-Filter - removes particles, sediments, and algae.

STEP 3: R.O. Pump - high pressure, stainless steel pump to boost water pressure to 150 lbs. for maximum membrane efficiency.

STEP 4: Reverse Osmosis Membrane - water is forced through a semi permeable, .0002 micron membrane, allowing only pure water molecules to pass.

STEP 5: Storage - water is stored in FDA approved tanks.

STEP 6: Repressure System - 20 GPM .

STEP 7: Post Carbon Filtration - water travels through a 4.5in x 20in coconut shell carbon block filter, polishing it for an exceptionally smooth taste.

STEP 8: Ultraviolet Sterilizer eliminates up to 99.9% of all bacteria.

Mini Skid

Features:

Powder coated steel frame
Pre-wired electrical panel
Carbon Pretreatment
5 Micron Pre-Filter: 4"x10" cartridge
Electronic Inlet Valve
High Pressure R.O. pump
Stainless Steel Membrane housing
Waste, Product, and Recycle stainless steel valves
Waste, Product, and Recycle meters
Pre and post filter gauges
Waste and recycle valves
Product and waste flow meters
All components and materials are either NSF/
FDA/UL/ETL approved

Options:

Feed Pump
TDS meter
Water meter

Specifications:

Feed water:

- Temperature: 35°-85°
- Pressure: 40-80 psi
- Total Dissolved Solids (TDS): 2000 ppm

Tolerance:

- Iron: 0.5 ppm
- Silica: 25 ppm@50%
- Recovery pH range: 3-11
- Water recovery—up to 60%
- Salt rejection—90-98%+